LU007UW-RI01



3	LECTRICAL FEATURES	M		
LED CHIP	SMD, CREE			
TOTAL LUMEN OUTPUT	700LM Warm White			
DIMMABILITY	NO			
POWER	7W	TEMP GLASS		
POWER SUPPLY	24V Dc			
BEAM ANGLE	20°	max 500kg		
LIFE SPAN	>50,000	5m		
CRI	>80			
This low voltage product needs to have an individual constant voltage 24V driver to operate.				

MECHANICAL FEATURES							
PACKING SIZE L X W X H	INSTALLATION	SLEEVE MATERIAL	WEIGHT	PROTECTION	Frame Material	DIFFUSER	BODY MATERIAL
160x160x90mm	Recessed Inground	PVC	1.6kg	IP68	Stainless Steel 316	Tempered Glass	Stainless Steel 316

PRODUCT IMAGE



AVAILABLE COLOR TEMPERATURE	9	
AVAILABLE COLOR TEMPERATURE	AVAILABLE COLOR TEMPERATUR	RE





EEC

APPLICATION PHOTO	
-------------------	--



2D LAYOUT



GENERAL FEATURES

Supper energy efficient.

2700

Features special optics to prevent the loss of the light over a distance.

Good choice to be used as opposing light in pools.

An ideal light for illuminating steps/swin outs/edged.

Can be installed in depth of max 3meters.

Available in single color or RGB.

3 years warranty.



