LU016UW-RI01



ELECTRICAL FEATURES						
LED CHIP	SMD, CREE					
TOTAL LUMEN OUTPUT	1600LM Warm White					
DIMMABILITY	NO					
POWER	16W	TEMP GLASS				
POWER SUPPLY	24V Dc					
BEAM ANGLE	20°	max 500kg				
LIFE SPAN	>50,000	5m				
CRI	>80					
This low voltage product needs to have an individual constant voltage 24V driver to operate.						

MECHANICAL FEATURES									
PACKING SIZE L X W X H	INSTALLATION	SLEEVE MATERIAL	WEIGHT	PROTECTION	FRAME MATERIAL	DIFFUSER	BODY MATERIAL		
190x190x90mm	Recessed Inground	PVC	2.2kg	IP68	Stainless Steel 316	Tempered Glass	Stainless Steel 316		

PRODUCT IMAGE



AVAILABLE COLOR TEMPERATURE 2700 3000 4000 5000



EEC Α

IP68

2D LAYOUT



APPLICATION PHOTO

GENERAL FEATURES

Supper energy efficient.

Features special optics to prevent the loss of the light over a distance.

Good choice to be used as opposing light in pools.

An ideal light for illuminating steps/swin outs/edged

Can be installed in depth of max 3meters.

Available in single color or RGB.

3 years warranty.



