LU020FL-SQ01



ELECTRICAL FEATURES					
LED CHIP	COB, CREE				
TOTAL LUMEN OUTPUT	2000LM Warm White				
DIMMABILITY	NO				
POWER	20W				
POWER SUPPLY	12V AC/DC				
BEAM ANGLE	25°				
LIFE SPAN	>50,000				
CRI	>80				
AVAILABLE COLOR TEMPERATURE					

MECHANICAL FEATURES									
PACKING SIZE L X W X H	INSTALLATION	BRACKET MATERIAL	WEIGHT	PROTECTION	DIFFUSER	BODY MATERIAL			
180x180x140mm	Mounting with Bracket	Die casting Aluminum	1.5kg	IP66	Tempered Glass	Die casting Aluminum			

PRODUCT IMAGE



\mathbf{A}	$\mathbf{V}\mathbf{\Lambda}$	ПΛС	ЭΙС	\sim 0	\bigcirc D		DED	ATUR	1
VΑN	VA	II VAN	DLE	GUI	JUK.	= 11/1			1=



5000



CLASS III

EEC





APPLICATION PHOTO

3000





2D LAYOUT



GENERAL FEATURES

Unique design with a die casting aluminum bracket for surface mounting.

Supper energy efficient.

2700

Available in 100-240V AC, 50-60Hz.

Ideal for all outdoor flood lighting applications.

Can be mounted on the poles for outdoor area lighting.

3 years warranty.



