LU045RB20-W18



| ELECTRICAL FEATURES | | | | | |
|-----------------------|--|--|--|--|--|
| LED CHIP | Samsung | | | | |
| NUMBER OF LED/ METER | 120pcs. /meter | | | | |
| DIMMABILITY | YES | | | | |
| POWER | 9W / Meter | | | | |
| POWER SUPPLY | 24V DC | | | | |
| CRI | >60 | | | | |
| BEAM ANGLE | 120° | | | | |
| OPERATING TEMPERATURE | -30° ~ +55° | | | | |
| LIFE SPAN | >5000 | | | | |
| TOTAL LUMEN OUTPUT | Warm White: 450LM per meter Day Light: 500LM per meter Cool White: 550LM per meter | | | | |
| Note | This low voltage product needs to have an individual constant voltage 24V driver to operate. | | | | |

AVAILABLE COLOR TEMPERATURE

| 2700K | 3000K | 4000K | 5000K | RED | GREEN | BLUE |
|-------|-------|-------|-------|-----|-------|------|
| | | | | | | |

GENERAL FEATURES

Designed to be bended.

Accurate color temperature.

Energy efficient.

Well designed for proper thermal management and heat dissipation.

Suitable for all indoor applications using our aluminum profiles.

3 years warranty





























PRODUCT IMAGE



APPLICATION PHOTO



CUTTING SIZE

