LU072RS20-C60



PCB MATERIAL

Copper

ELECTRICAL FEATURES	
LED CHIP	Samsung
NUMBER OF LED/ METER	60pcs. /meter
DIMMABILITY	YES
POWER	14.4W / Meter
POWER SUPPLY	24V DC
CRI	>80
BEAM ANGLE	120°
OPERATING TEMPERATURE	-30° ~ +55°
LIFE SPAN	>5000
TOTAL LUMEN OUTPUT	Warm White: 1296LM per meter Day Light: 1440LM per meter Cool White: 1584LM per meter
Note	This low voltage product needs to have an individual constant voltage 24V driver to operate.

AVAILABLE COLOR TEMPERATURE

GENERAL FEATURES

















APPLICATION PHOTO

PACKING SIZE

LXWXH

240x220x15mm



CUTTING SIZE

16mm

SEAL-OUT

MATERIAL

No

100mm

100mm



PRODUCT IMAGE

STRIP

THICKNESS

2mm

LENGHT OF REEL

5m

MECHANICAL FEATURES

INSTALLATION PROTECTION

IP20

Stickable with

3M adhesive

WEIGHT

200gr









Energy efficient.





Designed to be bended to all sides.

Accurate color temperature.





Well designed for proper thermal management and heat dissipation.

Suitable for all indoor applications using our aluminum profiles.











