# LU026WDBL-SQ01



ELECTRICAL FEATURES					
LED CHIP	SMD, LED				
TOTAL LUMEN OUTPUT	1820LM Warm White	TEMP. GLASS			
DIMMABILITY	NO	[FEO]			
POWER	26W	EEC A			
POWER SUPPLY	190 - 260V AC, 50 - 60Hz				
BEAM ANGLE	1Sided	IK08			
LIFE SPAN	>40,000Hrs	CLASS			
CRI	>80	I			
POWER FACTOR	0.96	IP66			
AVAILABLE COLOR TEARER ATURE					

MECHANICAL FEATURES								
PACKING SIZE L X W X H	INSTALLATION	BODY MATERIAL	WEIGHT	PROTECTION	FINISH	DIFFUSER		
650x220x130mm	Floor Mounted	Coated Timber wood	2.8kg	IP66	Wooden	Tempered Glass		

### **PRODUCT IMAGE**



### **2D LAYOUT**

### **APPLICATION PHOTO**

4000

5000

**AVAILABLE COLOR TEMPERATURE** 



## **GENERAL FEATURES**

Marine Grade body finish coated timber wood.

Very versatile luminare for outdoor lighting applications.

3000

Easy Installation

2700

3 year warranty

