

## ELECTRICAL FEATURES

|                    |                          |
|--------------------|--------------------------|
| LED CHIP           | OSRAM                    |
| TOTAL LUMEN OUTPUT | 4000LM Warm White        |
| DIMMABILITY        | NO                       |
| POWER              | 40W                      |
| POWER SUPPLY       | 100 - 277V AC, 50 - 60Hz |
| BEAM ANGLE         | 360°                     |
| LIFE SPAN          | >50,000                  |
| CRI                | >80                      |

## AVAILABLE COLOR TEMPERATURE



## APPLICATION PHOTO



## GENERAL FEATURES

- Anti-corrosion powder coated body finish.
- Uniform illumination on ground surface.
- Suitable for illuminating path and urban.
- Easy to maintain.
- 3 years warranty.



IK10

IP65

CLASS I

ETL

LVD

RoHS

BG

GS

EEC A

CE

## MECHANICAL FEATURES

| PACKING SIZE<br>L X W X H | INSTALLATION | OPTIC<br>MATERIAL               | WEIGHT | PROTECTION | FINISH                 | DIFFUSER                   | BODY MATERIAL           |
|---------------------------|--------------|---------------------------------|--------|------------|------------------------|----------------------------|-------------------------|
| 500x500x260mm             | Pole Mounted | High Pressure<br>Tempered Glass | 12.3kg | IP65       | Textured<br>Matt Black | Prominent<br>Polycarbonate | Die casting<br>Aluminum |

## PRODUCT IMAGE



## 2D LAYOUT

