LU045PLO-L01



| | | | | | | | | | feel the | difference | |
|--|-------------------------------------|----------------|---------------------|--------------|-----------|---------|------------|-----------------|-------------|---------------|--|
| ELECTRICAL FEATURES | | <u>M</u> | MECHANICAL FEATURES | | | | | | | | |
| LIGHT SOURCE | PHILIPS LED | | PRODUCT HEIGHT | INSTALLATION | REFLECTOR | IK Rate | PROTECTION | FINISH | DIFFUSER | BODY MATERIAL | |
| TOTAL LUMEN OUTPUT | 4500lm Warm White | TEMP. GLASS | 3-5m Options | Pole | Aluminum | IK08 | IP65 | Dark Grey/Black | Temp. Glass | Aluminum | |
| CRI | >80 | IK08 | | Mounted | | | | | | | |
| POWER | 45W (Can be 40-60W by order) | | PRODUCT IMAGE | | | | | DIMENSIONS | | | |
| POWER SUPPLY | 180 - 240V AC, 50 - 60Hz | IP65 | | | | | | 150 | | | |
| POWER FACTOR | >92 | CLASS | | | | | | 81 | 600 | | |
| LIFE SPAN | >50,000Hrs | CLASS I | | | | | | 7 | | † | |
| | | RoHS | | | | | | | | | |
| AVAILABLE COLOR TEMPERATURE | | CE | | | | | | | | | |
| 2700 | 3000 4000 5000 GENERAL FEATURES | | | | ı | | | | | | |
| cast aluminum with anti-corrosion and UV-proof powder coating | | | | | | | | | | 2000 | |
| Included with pole and lighting head which can install in the top rad of the pole. (Pole height can be customised) | | | | | | | | | | 47 | |
| Surface features anti-ageing electrostatic spray processing for more reliability. | | | | | | | | | | | |
| Suitable to use in outdoor spaces like parks, public spaces etc. | | | | | | | | | | | |
| Tempered glass diffus | ser for maximum light distribution. | | | | | | | | | | |
| 3 years warranty. | | | | | | | | | | | |
| | | | | | | | | | , | | |