
LU012FLDS-RU01



OUTDOOR ADJUSTABLE LED FLOOD LIGHT





RoHS

Description

Compact architectural and stylish outdoor innovative projector for variety of floodlighting applications, ideal for accent lighting, available in different sizes/ wattage options, with high power LED, high-pressure die-casting aluminium body, stainless steel screws, high strength 6mm toughened glass, extremely narrow to wide beam options, rotationally symmetric light distribution, integrated power supply with dimmable options.

Electrical Features

IP66

Wattage	12W
Light Source	Cree Cob LED
Output Lumen	1200lm
Input Voltage	220V AC with built-in Dali driver
LED Life Span	50,000Hrs
Control	On/Off or DALI Dimmable

Correlated Color Temperature (CCT)



3000K WW



5700K CW

*Other Color Temperatures can be customised as per order.

Beam Angle















* Other Beam angles can be customised as per order.

Color Finish

Powder coated architectural bronze finish

Mechanical Features

Installation	Surface Mounted
Body Material	Die-cast Aluminum
Bracket Material	Die-cast Aluminum
Diffuser	Clear Tempered glass
Ingress Protection	IP66
Dimension	As per drawing

LU012FLDS-RU01



Installation Method



LU012FLDS-RU01



Accessories



Application



Project Name: Czech Republic at Expo2020, Dubai, UAE.